



TUV T8

TUV 75W HO 1SL

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

Product data

• General Characteristics

System Description	High Output
Cap-Base	G13
Bulb	T26
Main Application	Disinfection
Useful Life	9000 hr

• Electrical Characteristics

Lamp Wattage	75 W
Lamp Wattage Technical	75 W
Lamp Voltage	110 V
Lamp Current	0.84 A

• Environmental Characteristics

Mercury (Hg) Content	2.0 mg
----------------------	--------

• Light Technical Characteristics

Color Designation (text)	-
--------------------------	---

• UV-related Characteristics

UV-C Radiation	25.5 W
----------------	--------


• Product Dimensions

Base Face to Base Face A	1199.4 (max) mm
Insertion Length B	1204.1 (min), 1206.5 (max) mm
Overall Length C	1213.6 (max) mm
Diameter D	28 (max) mm


• Product Data

Order code	928049404003
Full product code	928049404003
Full product name	TUV 75W HO 1SL
Order product name	TUV 75W HO 1SL/6
Pieces per pack	1
Packing configuration	6
Packs per outerbox	6
Bar code on pack - EAN1	8711500618511
Bar code on outerbox - EAN3	8711500618528
Logistic code(s) - 12NC	928049404003
Net weight per piece	173.000 gr



Dimensional drawing



Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TUV TL-D 75W HO	1199.4	1204.1	1206.5	1213.6	28



Photometric data



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, July 25
data subject to change